

MULLION MATE®

ADJUSTABLE PARTITION WALL GAP CLOSURES

Mullion Mate[®] is an adjustable partition wall gap closure that creates the perfect transition between window mullions or windows and partition walls.

DESIGN FEATURES & BENEFITS

- An aesthetically pleasing finish over traditional drywall solutions
- Installs directly against the window mullion or window
- Provides noise reduction between rooms See STC (Sound Transmission Class) Data on page 3
- Provides an expansion and contraction feature at the building perimeter
- Fills a wide range of gaps (See gap sizes on pages 4 & 5)
- Can be factory cut to desired height or shipped in 10' or 16' stock lengths
- Optional Partition Wall End Caps are available to finish the partition wall

For more information & details visit: WWW.MULLIONMATE.COM



Installation Benefits

- Saves on labor costs ... installs in less than 5 minutes
- Arrives on-site fully assembled with insulation and gasket for quick installation
- Arrives with factory finish to match window mullion or wall finish
- · Reduces construction debris and clean-up







ACOUSTICAL

ANTIMICROBIAL

DURABLE









CLEANABLE

SEISMIC


Installation Options



WALL-TO-MULLION



WALL-TO-GLASS



Wall-to-Glass (Field Notch)

Mullion Mate® installs in 5 minutes or less, significantly reducing installation time and labor.

WATCH INSTALLATION VIDEOS







WALL-TO-MULLION

WALL-TO-GLASS


FINISH OPTIONS

- Anodized Finish
 - ° Clear
 - Medium Bronze
 - ° Dark Bronze
- AAMA 2604 powder coated in standard or custom colors
 - ° Meets AAMA 2604 Standards
 - ° All Powders are Antimicrobial
- AAMA 2605 powder coated in standard or custom colors
 - ° Meets AAMA 2605 Standards
 - ° Available in Antimicrobial Powder
- · Field paintable finish

SOUND ATTENUATION

Mullion Mate® can be provided in various options to accommodate your sound requirements.


- Series 30 Composite STC:
 - Installed against the window mullion = 35 STC
 - ° Installed against the window = 37 STC
- Series 40 Composite STC:
 - ° Installed against the window mullion = 38 STC
 - ° Installed against the window = 56 STC
- Series 60 Composite STC:
 - Installed on each side of window mullion at window against glass = 60 STC
- All testing per ASTM E90-09 (2016) & ASTM E413-16
 utilizing actual construction installation conditions,
 including glass to partition wall and mullion to
 partition wall
- See Gordon's White Paper (STC Acoustics)




Mullion Mate® Profiles

MULLION MATE SERIES 60*

- · Closes Gaps from 4" up to 7"
- Double Mullion Mate® design surrounds the window mullion, increasing STC up to 60.



* Patent Pending



SERIES 60 SIZES

Mullion Mate® 4


4" minimum to 5-7/16" maximum opening


Mullion Mate® 5.5


5-1/2" minimum to 7" maximum opening

MULLION MATE SERIES 40

- Closes Gaps from 2" up to 14"
- · Provides up to 56 STC







SERIES 40 SIZES

Mullion Mate® 2 – 2" minimum to 2-15/16" maximum opening

Mullion Mate® 3 – 3" minimum to 3-15/16" maximum opening

Mullion Mate® 4 - 4" minimum to 4-15/16" maximum opening


Mullion Mate® **5** – 5" minimum to 6-15/16" maximum opening **Mullion Mate**® **7** – 7" minimum to 8-15/16" maximum opening


Mullion Mate® 9 - 9" minimum to 14" maximum opening


Multiple units are pre-assembled or spliced for larger openings and heights.

MULLION MATE SERIES 30

- Closes Gaps from 2" up to 14"
- Provides up to 37 STC










PARTITION WALL END CAPS

- Creates a great transition between the Partition Wall and Mullion Mate®.
- · Sized to fit your wall



EXTRUDED MULLION MATE®	
PART #	"A"
MMEC-375	3-3/4"
MMEC-487	4-7/8"
MMEC-600	6"
MMEC-725	7-1/4"





BRAKE FORMED MULLION MATE® END CAPS	
"A"	
5-1/8"	
5-1/4"	
5-1/2"	
6-1/8"	
8-1/2"	

SERIES 30 SIZES

Mullion Mate® 2 - 2" minimum to 2-15/16" maximum opening

Mullion Mate® 3 - 3" minimum to 3-15/16" maximum opening

Mullion Mate® 4 - 4" minimum to 4-15/16" maximum opening

Mullion Mate® 5 - 5" minimum to 6-15/16" maximum opening

Mullion Mate® 7 - 7" minimum to 8-15/16" maximum opening

Mullion Mate® 9 - 9" minimum to 14" maximum opening

Multiple units are pre-assembled or spliced for larger openings and heights.







EXTERIOR









CLEANROOM



SECURITY

IMPASSIONED INNOVATION

Since established, in 1964, Gordon, Inc. has delivered innovative architectural and engineered solutions for interior and exterior applications, leading the industry's needs with next-level technologies and custom approaches to complex challenges. Advancing Architecture with Impassioned Innovation, our people, passion and expertise have allowed us to create award-winning solutions for multiple markets. Like your projects, we are anything but standard.



