



Quiet Coordinates Performance

ACOUSTICAL TREATMENT DETAILS					1/3 OCTAVE CENTER FREQUENCY (Absorption Coefficient)																		ABSORPTION TOTALS		
SYSTEM	DESCRIPTION	FACING	TOTAL AREA TESTED (FT ²)	MOUNTING	100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000	5000	NRC	SAA	SABINS*
Quiet Coordinates Wall Panel	2" Thick x 2 lb. Density	White Matte	72	A, Flat surf	0.28	0.33	0.33	0.51	0.63	0.85	0.91	0.99	1.05	1.05	1.06	1.06	1.03	1.01	0.98	0.97	0.98	0.97	0.90	0.93	66.78
Quiet Coordinates Wall Panel	2" Thick x 1.8 lb/3 lb. Dual Den	White Matte	72	A, Flat surf	0.19	0.32	0.35	0.48	0.64	0.87	0.97	1.06	1.07	1.08	1.08	1.07	1.05	1.03	0.99	0.99	1.04	1.05	0.95	0.95	68.34
Quiet Coordinates Wall Panel	2" Thick x 1.8 lb/3 lb. Dual Den	White Matte	72	E-400 Air gap, Cloud	0.98	0.86	0.86	0.97	0.98	0.99	0.93	0.87	1.02	1.04	1.01	1.03	1.02	1.03	1.05	1.05	1.09	1.06	0.95	1.00	71.64
Quiet Coordinates Impact Plus	2" Thick x 1.8 lb/3 lb. Dual Den	Perforated Plastic	72	D-5	0.29	0.28	0.30	0.43	0.54	0.81	0.90	0.99	1.03	1.04	1.02	1.00	0.95	0.94	0.91	0.85	0.90	0.83	0.85	0.88	63.36
* Represents total Sabins for total area tested																									



5023 Hazel Jones Rd.
Bossier City, LA 71111
www.gordon-inc.com